Rings, drums and curves, GEN 27

Curve 275

GEN 27 quarter-radius LED linear light

Project	
Type	
Date	



Curve 275 is a quarter-radius linear luminaire in the Dense 275 profile. Curved sections link with straight Dense and Sense 275 runs to draw S-shapes, ovals and closed loops.

Lumen output	1,840 to 7,695 lm
Colour temperature	2700K / 3000K / 3500K / 4000K / 5000K, selectable
Wattage	16 to 57 W

ETL | 5-year warranty

CURVE 275





Can be linearly spliced with
DENSE / SENSE 275 on Page P20

GEAR LINK

CURVE 275

GEN27 1/4 Radius LED Linear Light.

Specifications

Switch Select
1,840 - 7,695 Lumens

CCT Select
2700K/3000K/3500K/
4000K /5000K CCT

Wattage Select
16 - 57 Watts


Intertek

5 YEAR WARRANTY

Mounting



Pendant Mount



Features



Model No.	Size	Wattage Select	Nominal Efficacy	Output Lumen	CCT Select	Input Voltage	Dimming	CRI
WL-27LSUDS12 -YY	R12"x3.15"H (R300xH80mm)	/	/	/	/	/	/	/
WL-27LS1827WB5D1HV5A-90-YY	R18"x3.15"H (R450xH80mm)	16W/21W/27W Select	1840/2415/3105lm	115 lm/W	2700K-3000K-3500K-4000K-5000K-5 CCT Select	120-347V	0-10V (1-100%)	CRI>90
WL-27LS2437WB5D1HV5A-90-YY	R24"x3.15"H (R600xH80mm)	22W/30W/37W Select	2530/3450/4255lm					
WL-27LS3047WB5D1HV5A-90-YY	R30"x3.15"H (R750xH80mm)	28W/38W/47W Select	3220/4370/5405lm					
WL-27LS3657WB5D1HV5A-90-YY	R36"x3.15"H (R900xH80mm)	34W/46W/57W Select	3910/5290/6555lm					
WL-27LS1827WB5D1HV5A-80-YY	R18"x3.15"H (R450xH80mm)	16W/21W/27W Select	2160/2835/3645lm	135 lm/W				CRI>80
WL-27LS2437WB5D1HV5A-80-YY	R24"x3.15"H (R600xH80mm)	22W/30W/37W Select	2970/4050/4995lm					
WL-27LS3047WB5D1HV5A-80-YY	R30"x3.15"H (R750xH80mm)	28W/38W/47W Select	3780/5130/6345lm					
WL-27LS3657WB5D1HV5A-80-YY	R36"x3.15"H (R900xH80mm)	34W/46W/57W Select	4590/6210/7695lm					